

Wikiprint Book

Title: The Trac Ticket Workflow System

Subject: Tibusay Publicaciones - TracWorkflow

Version: 2

Date: 17/05/24 07:57:31

Table of Contents

The Trac Ticket Workflow System	3
The Default Ticket Workflow	3
Environments upgraded from 0.10	3
Environments created with 0.11	3
Additional Ticket Workflows	3
Basic Ticket Workflow Customization	3
Example: Adding optional Testing with Workflow	4
How to combine the tracopt.ticket.commit_updater with the testing workflow	5
Example: Add simple optional generic review state	5
Example: Limit the resolution options for a new ticket	6
Advanced Ticket Workflow Customization	6
Adding Workflow States to Milestone Progress Bars	6
Ideas for next steps	6

The Trac Ticket Workflow System

The Trac ticket system provides a configurable workflow.

The Default Ticket Workflow

Environments upgraded from 0.10

When you run `trac-admin <env> upgrade`, your `trac.ini` will be modified to include a `[ticket-workflow]` section. The workflow configured in this case is the original workflow, so that ticket actions will behave like they did in 0.10.

Graphically, that looks like this:

Enable JavaScript to display the workflow graph.

There are some significant "warts" in this; such as accepting a ticket sets it to 'assigned' state, and assigning a ticket sets it to 'new' state. Perfectly obvious, right? So you will probably want to migrate to "basic" workflow; [contrib/workflow/migrate_original_to_basic.py](#) may be helpful.

Environments created with 0.11

When a new environment is created, a default workflow is configured in your `trac.ini`. This workflow is the basic workflow (described in `basic-workflow.ini`), which is somewhat different from the workflow of the 0.10 releases.

Graphically, it looks like this:

Enable JavaScript to display the workflow graph.

Additional Ticket Workflows

There are several example workflows provided in the Trac source tree; look in [contrib/workflow](#) for `.ini` config sections. One of those may be a good match for what you want. They can be pasted into the `[ticket-workflow]` section of your `trac.ini` file. However if you have existing tickets then there may be issues if those tickets have states that are not in the new workflow.

Here are some [diagrams](#) of the above examples.

Basic Ticket Workflow Customization

Note: Ticket "statuses" or "states" are not separately defined. The states a ticket can be in are automatically generated by the transitions defined in a workflow. Therefore, creating a new ticket state simply requires defining a state transition in the workflow that starts or ends with that state.

Create a `[ticket-workflow]` section in `trac.ini`. Within this section, each entry is an action that may be taken on a ticket. For example, consider the `accept` action from `simple-workflow.ini`:

```
accept = new,accepted -> accepted
accept.permissions = TICKET_MODIFY
accept.operations = set_owner_to_self
```

The first line in this example defines the `accept` action, along with the states the action is valid in (`new` and `accepted`), and the new state of the ticket when the action is taken (`accepted`). The `accept.permissions` line specifies what permissions the user must have to use this action. The `accept.operations` line specifies changes that will be made to the ticket in addition to the status change when this action is taken. In this case, when a user clicks on `accept`, the ticket owner field is updated to the logged in user. Multiple operations may be specified in a comma separated list.

The available operations are:

- **del_owner** -- Clear the owner field.
- **set_owner** -- Sets the owner to the selected or entered owner. Defaults to the current user. When `[ticket] restrict_owner = true`, the select will be populated with users that have `TICKET_MODIFY` permission and an authenticated session.
 - `actionname.set_owner` may optionally be set to a comma delimited list of users that will be used to populate the select, or a single user.
- **set_owner_to_self** -- Sets the owner to the logged in user.
- **del_resolution** -- Clears the resolution field
- **set_resolution** -- Sets the resolution to the selected value.

`actionname.set_resolution` may optionally be set to a comma delimited list or a single value. Example:

```
resolve_new = new -> closed
resolve_new.name = resolve
resolve_new.operations = set_resolution
resolve_new.permissions = TICKET_MODIFY
resolve_new.set_resolution = invalid,wontfix
```

- **leave_status** -- Displays "leave as <current status>" and makes no change to the ticket.

Note: Specifying conflicting operations (such as `set_owner` and `del_owner`) has unspecified results.

In this example, we see the `.name` attribute used. The action here is `resolve_accepted`, but it will be presented to the user as `resolve`.

```
resolve_accepted = accepted -> closed
resolve_accepted.name = resolve
resolve_accepted.permissions = TICKET_MODIFY
resolve_accepted.operations = set_resolution
```

For actions that should be available in all states, `*` may be used in place of the state. The obvious example is the `leave` action:

```
leave = * -> *
leave.operations = leave_status
leave.default = 1
```

This also shows the use of the `.default` attribute. This value is expected to be an integer, and the order in which the actions are displayed is determined by this value. The action with the highest `.default` value is listed first, and is selected by default. The rest of the actions are listed in order of decreasing `.default` values. If not specified for an action, `.default` is 0. The value may be negative.

There are a couple of hard-coded constraints to the workflow. In particular, tickets are created with status `new`, and tickets are expected to have a `closed` state. Further, the default reports/queries treat any state other than `closed` as an open state.

Workflows can be visualized by rendering them on the wiki using the [Workflow macro](#).

Workflows can also be visualized using the `contrib/workflow/workflow_parser.py` script. The script outputs `.dot` files that [GraphViz](#) understands. The script can be used as follows (your install path may be different):

```
cd /var/local/trac_devel/contrib/workflow/
sudo ./showworkflow /srv/trac/PlannerSuite/conf/trac.ini
```

And then open up the resulting `trac.pdf` file created by the script (it will be in the same directory as the `trac.ini` file).

After you have changed a workflow, you need to restart apache for the changes to take effect. This is important, because the changes will still show up when you run your script, but all the old workflow steps will still be there until the server is restarted.

Example: Adding optional Testing with Workflow

By adding the following to your [ticket-workflow] section of `trac.ini` you get optional testing. When the ticket is in `new`, `accepted` or `needs_work` status you can choose to submit it for testing. When it's in the testing status the user gets the option to reject it and send it back to `needs_work`, or pass the testing and send it along to `closed`. If they accept it then it gets automatically marked as `closed` and the resolution is set to `fixed`. Since all the old work flow remains, a ticket can skip this entire section.

```
testing = new,accepted,needs_work,assigned,reopened -> testing
testing.name = Submit to reporter for testing
testing.permissions = TICKET_MODIFY

reject = testing -> needs_work
reject.name = Failed testing, return to developer

pass = testing -> closed
pass.name = Passes Testing
pass.operations = set_resolution
pass.set_resolution = fixed
```

How to combine the `tracopt.ticket.commit_updater` with the testing workflow

The [tracopt.ticket.commit_updater](#) is the optional component that [replaces the old trac-post-commit-hook](#), in Trac 0.12.

By default it reacts on some keywords found in changeset message logs like *close*, *fix* etc. and performs the corresponding workflow action.

If you have a more complex workflow, like the testing stage described above and you want the *closes* keyword to move the ticket to the *testing* status instead of the *closed* status, you need to adapt the code a bit.

Have a look at the [Trac 0.11 recipe](#) for the `trac-post-commit-hook`, this will give you some ideas about how to modify the component.

Example: Add simple optional generic review state

Sometimes Trac is used in situations where "testing" can mean different things to different people so you may want to create an optional workflow state that is between the default workflow's `assigned` and `closed` states, but does not impose implementation-specific details. The only new state you need to add for this is a `reviewing` state. A ticket may then be "submitted for review" from any state that it can be reassigned. If a review passes, you can re-use the `resolve` action to close the ticket, and if it fails you can re-use the `reassign` action to push it back into the normal workflow.

The new `reviewing` state along with its associated `review` action looks like this:

```
review = new,assigned,reopened -> reviewing
review.operations = set_owner
review.permissions = TICKET_MODIFY
```

Then, to integrate this with the default Trac 0.11 workflow, you also need to add the `reviewing` state to the `accept` and `resolve` actions, like so:

```
accept = new,reviewing -> assigned
[...]
```

```
resolve = new,assigned,reopened,reviewing -> closed
```

Optionally, you can also add a new action that allows you to change the ticket's owner without moving the ticket out of the `reviewing` state. This enables you to reassign review work without pushing the ticket back to the new status.

```
reassign_reviewing = reviewing -> *
reassign_reviewing.name = reassign review
reassign_reviewing.operations = set_owner
reassign_reviewing.permissions = TICKET_MODIFY
```

The full `[ticket-workflow]` configuration will thus look like this:

```
[ticket-workflow]
accept = new,reviewing -> assigned
accept.operations = set_owner_to_self
accept.permissions = TICKET_MODIFY
leave = * -> *
leave.default = 1
leave.operations = leave_status
reassign = new,assigned,accepted,reopened -> assigned
reassign.operations = set_owner
reassign.permissions = TICKET_MODIFY
reopen = closed -> reopened
reopen.operations = del_resolution
reopen.permissions = TICKET_CREATE
resolve = new,assigned,reopened,reviewing -> closed
resolve.operations = set_resolution
resolve.permissions = TICKET_MODIFY
review = new,assigned,reopened -> reviewing
review.operations = set_owner
review.permissions = TICKET_MODIFY
reassign_reviewing = reviewing -> *
reassign_reviewing.operations = set_owner
reassign_reviewing.name = reassign review
reassign_reviewing.permissions = TICKET_MODIFY
```

Example: Limit the resolution options for a new ticket

The above `resolve_new` operation allows you to set the possible resolutions for a new ticket. By modifying the existing resolve action and removing the new status from before the `->` we then get two resolve actions. One with limited resolutions for new tickets, and then the regular one once a ticket is accepted.

```
resolve_new = new -> closed
resolve_new.name = resolve
resolve_new.operations = set_resolution
resolve_new.permissions = TICKET_MODIFY
resolve_new.set_resolution = invalid,wontfix,duplicate

resolve = assigned,accepted,reopened -> closed
resolve.operations = set_resolution
resolve.permissions = TICKET_MODIFY
```

Advanced Ticket Workflow Customization

If the customization above is not extensive enough for your needs, you can extend the workflow using plugins. These plugins can provide additional operations for the workflow (like `code_review`), or implement side-effects for an action (such as triggering a build) that may not be merely simple state changes. Look at [sample-plugins/workflow](#) for a few simple examples to get started.

But if even that is not enough, you can disable the `ConfigurableTicketWorkflow` component and create a plugin that completely replaces it.

Adding Workflow States to Milestone Progress Bars

If you add additional states to your workflow, you may want to customize your milestone progress bars as well. See [TracIni](#).

Ideas for next steps

New enhancement ideas for the workflow system should be filed as enhancement tickets against the `ticket_system` component. You can also document ideas on the [TracIdeas/TracWorkflow](#) page. Also look at the [AdvancedTicketWorkflowPlugin](#) as it provides experimental operations.